

Features :

- Isolated mounting base 3000V~
- Pressure contact technology with Increased power cycling capability
- Space and weight saving

Typical Applications

- AC/DC Motor drives
- DC supply for PWM inverter

V _{RSM}	V _{RRM}	Type
2100V	2000V	Mx135D200
2300V	2200V	Mx135D220
2600V	2500V	Mx135D250

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T _J (°C)	VALUE			UNIT
				Min	Type	Max	
I _{F(AV)}	Mean forward current	180° half sine wave 50Hz Single side cooled, T _C =100°C	150			135	A
I _{F(RMS)}	RMS forward current		150			212	A
I _{RRM}	Repetitive peak current	at V _{RRM}	150			12	mA
I _{FSM}	Surge forward current	10ms half sine wave V _R =0.6V _{RRM}	150			3.9	kA
I ² t	I ² t for fusing coordination					76	A ² s*10 ³
V _{FO}	Threshold voltage		150			0.83	V
r _F	Forward slope resistance					1.23	mΩ
V _{FM}	Peak forward voltage	I _{FM} =410A	25			1.41	V
R _{th(j-c)}	Thermal resistance Junction to case	At 180° sine Single side cooled				0.30	°C/W
R _{th(c-h)}	Thermal resistance case to heatsink	At 180° sine Single side cooled				0.08	°C/W
V _{iso}	Isolation voltage	50Hz, R.M.S, t=1min, I _{iso} :1mA(max)		3000			V
F _m	Terminal connection torque(M6)				6.0		N·m
	Mounting torque(M6)				6.0		N·m
T _{vj}	Junction temperature			-40		150	°C
T _{stg}	Stored temperature			-40		125	°C
W _t	Weight				320		g
Outline	M02						




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7






Fig.8


Outline:




MD135D



MR135D



MC135D



MH135D

