

**Features:**

- Isolated mounting base 2500V~
- Simple design, Module and SCR rectifier bridge, Small volume, light weight

**Typical Applications:**

- Supplies for DC power equipment
- Field supply for DC motors
- Inverter welder

V <sub>DRM</sub> , V <sub>RRM</sub>	品名
600V	MG150TH60S
800V	MG150TH80S
1000V	MG150TH100S
1200V	MG150TH120S
1400V	MG150TH140S
1600V	MG150TH160S
1800V	MG150TH180S


**Diode**

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T <sub>j</sub> (°C)	VALUE			UNIT
				Min	Type	Max	
I <sub>D</sub>	DC output current	Three-phase full wave rectifying circuit, T <sub>C</sub> =100°C	125			150	A
V <sub>RRM</sub>	Repetitive peak reverse voltage	tp=10ms	125	600		1800	V
I <sub>RRM</sub>	Repetitive peak current	at V <sub>RRM</sub>	125			8	mA
I <sub>FSM</sub>	Surge forward current	10ms half sine wave V <sub>R</sub> =0	125			1.3	kA
I <sup>2</sup> t	I <sup>2</sup> t for fusing coordination					8.45	10 <sup>3</sup> A <sup>2</sup> s
V <sub>FO</sub>	Threshold voltage		125			0.85	V
r <sub>F</sub>	Forward slope resistance					1.60	mΩ
V <sub>FM</sub>	Peak forward voltage	I <sub>FM</sub> =150A	25			1.40	V
R <sub>th(j-c)</sub>	Thermal resistance Junction to case	D.C. Single side cooled, per chip				0.15	°C/W
R <sub>th(c-h)</sub>	Thermal resistance case to heatsink	D.C. Single side cooled, per chip				0.07	°C/W
V <sub>iso</sub>	Isolation voltage	50Hz, R.M.S, t=1min, I <sub>iso</sub> : 1mA(max)		2500			V
F <sub>m</sub>	Terminal connection torque(M6)			3.5		5.0	N·m
	Mounting torque(M6)			3.5		5.0	N·m
T <sub>vj</sub>	Junction temperature			-40		125	°C
T <sub>stg</sub>	Stored temperature			-40		125	°C
W <sub>t</sub>	Weight				340		g
Outline	<b>M33</b>						


**Thyristor**

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T <sub>j</sub> (°C)	VALUE			UNIT
				Min	Type	Max	
I <sub>T(AV)</sub>	Mean on-state current	180° half sine wave 50Hz Single side cooled, T <sub>c</sub> =100°C	125			150	A
V <sub>DRM</sub> V <sub>RRM</sub>	Repetitive peak off-state voltage Repetitive peak reverse voltage	tp=10ms	125	600		1800	V
I <sub>DRM</sub> I <sub>RRM</sub>	Repetitive peak current	at V <sub>DRM</sub> at V <sub>RRM</sub>	125			40	mA
I <sub>TSM</sub>	Surge on-state current	10ms half sine wave V <sub>R</sub> =60%V <sub>RRM</sub>	125			1.3	kA
I <sup>2</sup> t	I <sup>2</sup> t for fusing coordination					8.45	A <sup>2</sup> s*10 <sup>3</sup>
V <sub>TO</sub>	Threshold voltage		125			0.85	V
r <sub>T</sub>	On-state slop resistance					1.6	mΩ
I <sub>GT</sub>	Gate trigger current	V <sub>A</sub> =12V, I <sub>A</sub> =1A	25	30		200	mA
V <sub>GT</sub>	Gate trigger voltage			0.6		2.5	V
I <sub>H</sub>	Holding current			10		250	mA
I <sub>L</sub>	Latching current					1000	mA
V <sub>GD</sub>	Non-trigger gate voltage	V <sub>DM</sub> =67%V <sub>DRM</sub>	125			0.30	V
V <sub>TM</sub>	Peak on-state voltage	I <sub>TM</sub> =450A	25			1.65	V
dv/dt	Critical rate of rise of off-state voltage	V <sub>DM</sub> =67%V <sub>DRM</sub>	125			500	V/μs
R <sub>th(j-c)</sub>	Thermal resistance Junction to case	D.C. Single side cooled, per chip				0.20	°C /W
R <sub>th(c-h)</sub>	Thermal resistance case to heatsink	D.C. Single side cooled, per chip				0.10	°C /W
V <sub>iso</sub>	Isolation voltage	50Hz,R.M.S,t=1min,I <sub>iso</sub> :1mA(MAX)		2500			V
F <sub>m</sub>	Terminal connection torque(M6)			3.5		5.0	N·m
	Terminal connection torque(M4)			1.5		2.5	N·m
	Mounting torque(M6)			3.5		5.0	N·m
T <sub>vj</sub>	Junction temperature			-40		125	°C
T <sub>stg</sub>	Stored temperature			-40		125	°C
W <sub>t</sub>	Weight				340		g
Outline	<b>M33</b>						

**Outline:**



**MG150TH\*\*S**



Unmarked dimensional tolerance: ±0.5mm

NIPS reserves the right to change specifications without notice.