

Features:

- Isolated mounting base3000V~
- Pressure contact technology with Increased power cycling capability
- Space and weight saving

Typical Applications

- Various rectifiers
- DC supply for PWM inverter

V_{RSM}	V_{RRM}	品名
2100V	2000V	Mx70D200
2300V	2200V	Mx70D220
2600V	2500V	Mx70D250

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	$T_j(^{\circ}\text{C})$	VALUE			UNIT
				Min.	Typ.	Max.	
$I_{F(AV)}$	Mean forward current	180° half sine wave 50Hz Single side cooled, $T_c=100^{\circ}\text{C}$	150			70	A
$I_{F(RMS)}$	RMS forward current		150			110	A
I_{RRM}	Repetitive peak current	at V_{RRM}	150			8	mA
I_{FSM}	Surge forward current	10ms half sine wave $V_R=0.6V_{RRM}$	150			1.80	kA
I^2t	I^2t for fusing coordination					16.2	$\text{A}^2\text{s} \times 10^3$
V_{FO}	Threshold voltage		150			0.85	V
r_F	Forward slope resistance					2.73	$\text{m}\Omega$
V_{FM}	Peak forward voltage	$I_{FM}=210\text{A}$	25			1.50	V
$R_{th(j-c)}$	Thermal resistance Junction to case	D.C.: Single side cooled per chip				0.55	$^{\circ}\text{C}/\text{W}$
$R_{th(c-h)}$	Thermal resistance case to heatsink	D.C.: Single side cooled per chip				0.20	$^{\circ}\text{C}/\text{W}$
V_{iso}	Isolation voltage	50Hz, R.M.S, t=1min, I_{iso} :1mA(max)		3000			V
F_m	Terminal connection torque(M5)			2.4		3.0	$\text{N}\cdot\text{m}$
	Mounting torque(M6)				6.0		$\text{N}\cdot\text{m}$
T_{vj}	Junction temperature			-40		150	$^{\circ}\text{C}$
T_{stg}	Stored temperature			-40		125	$^{\circ}\text{C}$
W_t	Weight				170		g
Outline		M01					




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6





Fig.7



Unmarked dimensional tolerance : $\pm 0.5\text{mm}$

MD70D**

MR70D**

MC70D**

