

Features

Low forward voltage drop

- High reverse voltage
- Hermetic metal cases with ceramic insulators

Typical Applications

- All purpose high power rectifier diodes
- High power resistance welding equipment
- Non-controllable and half-controllable rectifiers

 $I_{F(AV)}$ 1100A **V_{RRM} 2100 ~ 3000V** **I_{FSM} 15 kA** **I^2t 1125 10³A²S**

SYMBOL	CHARACTERISTIC	TEST CONDITIONS		T _j (°C)	VALUE			UNIT
					Min	Type	Max	
$I_{F(AV)}$	Mean forward current	180° half sine wave 50Hz Double side cooled,	T _C =85°C	160			1100	A
V_{RRM}	Repetitive peak reverse voltage	tp=10ms		160	2100		3000	V
I_{RRM}	Repetitive peak current	At V_{RRM}		160			50	mA
I_{FSM}	Surge forward current	10ms half sine wave		160			15	kA
I^2t	I^2t for fusing coordination	$V_R=0.6V_{RRM}$					1125	A ² s*10 ³
V_{FO}	Threshold voltage			160			0.87	V
r_F	Forward slope resistance						0.48	mΩ
V_{FM}	Peak forward voltage	$I_{FM}=1500A, F=18kN$		25			1.80	V
Q_{rr}	Recovery charge	$I_{FM}=1000A, tp=4000\mu s, di/dt=-20A/\mu s, V_R=100V$		160		2200		μC
$R_{th(j-c)}$	Thermal resistance Junction to case	D.C. double side cooled Clamping force 15.0kN					0.028	°C /W
$R_{th(c-h)}$	Thermal resistance case to heat sink						0.0075	
F_m	Mounting force				15		20	kN
T_{vj}	Junction temperature				-40		160	°C
T_{stg}	Stored temperature				-40		160	°C
W_t	Weight					320		g
Outline	P40							




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7

Outline:

