

Features

- Low forward voltage drop
- High reverse voltage
- Hermetic metal cases with ceramic insulators

I_{F(AV)} 1390A

Typical Applications

- All purpose high power rectifier diodes
- High power resistance welding equipment
- Non-controllable and half-controllable rectifiers
- Controlled rectifiers

V_{RRM} 1100 ~ 2000V

I_{FSM} 15 kA

I²t 1125 10³A²S

SYMBOL	CHARACTERISTIC	TEST CONDITIONS		T _J (°C)	VALUE			UNIT
					Min	Type	Max	
I _{F(AV)}	Mean forward current	180° half sine wave 50Hz Double side cooled,	T _C =85°C	175			1390	A
V _{RRM}	Repetitive peak reverse voltage	tp=10ms		175	1100		2000	V
I _{RRM}	Repetitive peak current	at V _{RRM}		175			40	mA
I _{FSM}	Surge forward current	10ms half sine wave		175			15	kA
I ² t	I ² t for fusing coordination	V _R =0.6V _{RRM}						1125
V _{FO}	Threshold voltage			175			0.85	V
r _F	Forward slope resistance							0.29
V _{FM}	Peak forward voltage	I _{FM} =2400A, F=15kN		25			2.0	V
Q _{rr}	Recovery charge	I _{FM} =1000A, tp=4000μs, di/dt=-20A/μs, V _R =100V		175		2000		μC
R _{th(j-c)}	Thermal resistance Junction to case	D.C. double side cooled Clamping force 15.0kN					0.035	°C/W
R _{th(c-h)}	Thermal resistance case to heat sink						0.008	
F _m	Mounting force				10		20	kN
T _{vj}	Junction temperature				-40		175	°C
T _{stg}	Stored temperature				-40		175	°C
W _t	Weight					240		g
Outline	P39							




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6





Fig.7

Outline:



Nlps reserves the right to change specifications without notice.