

Features

- Low forward voltage drop
- High reverse voltage
- Hermetic metal cases with ceramic insulators

Typical Applications

- All purpose high power rectifier diodes
- High power resistance welding equipment
- Non-controllable and half-controllable rectifiers
- Controlled rectifiers

 $I_{F(AV)}$ 1790A **V_{RRM} 1100 ~ 2000V** **I_{FSM} 18 kA** **I^2t 1620 10³A²S**

SYMBOL	CHARACTERISTIC	TEST CONDITIONS		$T_j(^{\circ}\text{C})$	VALUE			UNIT
					Min	Type	Max	
$I_{F(AV)}$	Mean forward current	180° half sine wave 50Hz Double side cooled,	$T_C=85^{\circ}\text{C}$	175			1790	A
V_{RRM}	Repetitive peak reverse voltage	$t_p=10\text{ms}$		175	1100		2000	V
I_{RRM}	Repetitive peak current	$V_{RM}=V_{RRM}$		175			50	mA
I_{FSM}	Surge forward current	10ms half sine wave		175			18	kA
I^2t	I^2t for fusing coordination	$V_R=0.6V_{RRM}$					1620	A ² s*10 ³
V_{FO}	Threshold voltage			175			0.90	V
r_F	Forward slope resistance						0.204	mΩ
V_{FM}	Peak forward voltage	$I_{FM}=3000\text{A}$, $F=18\text{kN}$		25			2.0	V
Q_{rr}	Recovery charge	$I_{FM}=1000\text{A}$, $t_p=4000\mu\text{s}$, $di/dt=-20\text{A}/\mu\text{s}$, $V_R=100\text{V}$		175		1900		μC
$R_{th(j-c)}$	Thermal resistance Junction to case	D.C. double side cooled Clamping force 18.0kN					0.028	°C/W
$R_{th(c-h)}$	Thermal resistance case to heat sink						0.0075	
F_m	Mounting force				15		20	kN
T_{vj}	Junction temperature				-40		175	°C
T_{stg}	Stored temperature				-40		175	°C
W_t	Weight					320		g
Outline	P40							




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7

Outline:

