


Features

- Center amplifying gate
- Metal case with ceramic insulator
- Low on-state and switching losses

Typical Applications

- AC controllers
- DC and AC motor control
- Controlled rectifiers

$I_{T(AV)}$ **1900A**
 V_{DRM}/V_{RRM} **400~1000V**
 I_{TSM} **29 kA**
 I^2t **4205 10³A²S**



SYMBOL	CHARACTERISTIC	TEST CONDITIONS		T _J (°C)	VALUE			UNIT
					Min	Type	Max	
I _{T(AV)}	Mean on-state current	180° half sine wave 50Hz Double side cooled	T _C =70°C				1900	
V _{DRM} V _{RRM}	Repetitive peak off-state voltage Repetitive peak reverse voltage	t _p =10ms		125	400		1000	V
I _{DRM} I _{RRM}	Repetitive peak current	at V _{DRM} at V _{RRM}		125			80	mA
I _{TSM}	Surge on-state current	10ms half sine wave		125			29	kA
I ² t	I ² t for fusing coordination	V _R =0.6V _{RRM}						4205
V _{TO}	Threshold voltage			125			0.89	V
r _T	On-state slope resistance							0.12
V _{TM}	Peak on-state voltage	I _{TM} =2550A, F=24kN		25			1.20	V
dv/dt	Critical rate of rise of off-state voltage	V _{DM} =0.67V _{DRM}		125			1000	V/μs
di/dt	Critical rate of rise of on-state current	V _{DM} = 67%V _{DRM} to2500A, Gate pulse t _r ≤0.5μs I _{GM} =1.5A		125			200	A/μs
Q _{rr}	Recovery charge	I _{TM} =2000A,t _p =2000μs, di/dt=-20A/μs, V _R =50V		125		1500		μC
I _{GT}	Gate trigger current			25	40		300	mA
V _{GT}	Gate trigger voltage	V _A =12V, I _A =1A			0.8		3.0	V
I _H	Holding current				20		300	mA
V _{GD}	Non-trigger gate voltage	V _{DM} =67%V _{DRM}		125	0.3			V
R _{th(j-c)}	Thermal resistance Junction to case	DC: double side cooled Clamping force 24kN					0.020	°C /W
R _{th(c-h)}	Thermal resistance case to heatsink						0.005	
F _m	Mounting force				19		26	kN
T _{stg}	Stored temperature				-40		140	°C
W _t	Weight					440		g
Outline	P11							




Fig1




Fig2




Fig3




Fig4




Fig5




Fig6




Fig7




Fig8





Fig9



Nlps reserves the right to change specifications without notice.