

Features

- Low forward voltage drop
- High reverse voltage
- Hermetic metal cases with ceramic insulators

I_{F(AV)} 3180A**V_{RRM} 200~1000 V****I_{FSM} 30 kA****I²t 4500 10³A²S****Typical Applications**

- All purpose high power rectifier diodes
- High power resistance welding equipment
- Non-controllable and half-controllable rectifiers
- Controlled rectifiers



SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T _j (°C)	VALUE			UNIT
				Min	Type	Max	
I _{F(AV)}	Mean forward current	180° half sine wave 50Hz Double side cooled,	T _C =85°C	190		3180	A
V _{RRM}	Repetitive peak reverse voltage	tp=10ms	190	200		1000	V
I _{RRM}	Repetitive peak current	at V _{RRM}	190			80	mA
I _{FSM}	Surge forward current	10ms half sine wave V _R =0.6V _{RRM}	190			30	kA
I ² t	I ² t for fusing coordination					4500	A ² s*10 ³
V _{FO}	Threshold voltage		190			0.79	V
r _F	Forward slope resistance					0.11	mΩ
V _{FM}	Peak forward voltage	I _{FM} =2000A, F=24kN	190			1.01	V
Q _{rr}	Recovery charge	I _{FM} =2000A, tp=2000μs, di/dt=-20A/μs, V _R =50V	190		3300		μC
R _{th(j-c)}	Thermal resistance Junction to case	DC double side cooled Clamping force 24.0 kN				0.020	°C /W
R _{th(c-h)}	Thermal resistance case to heat sink					0.005	
F _m	Mounting force			19		26	kN
T _{stg}	Stored temperature			-40		190	°C
W _t	Weight				440		g
Outline		P42					




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7

