


**Features**

- Interdigitated amplifying gates
- Fast turn-on and high di/dt
- Low switching losses

**Typical Applications**

- Inductive heating
- Electronic welders
- Self-commutated inverters

$I_{T(AV)}$	<b>750A</b>
$V_{DRM}/V_{RRM}$	<b>800~1800V</b>
$t_q$	<b>18~50<math>\mu</math>s</b>
$I_{TSM}$	<b>9.5kA</b>
$I^2t$	<b>451 10<sup>3</sup>A<sup>2</sup>S</b>



SYMBOL	CHARACTERISTIC	TEST CONDITIONS		T <sub>J</sub> (°C)	VALUE			UNIT
					Min	Type	Max	
$I_{T(AV)}$	Mean on-state current	180° half sine wave 50Hz Double side cooled,	$T_C=55^\circ\text{C}$	125			750	A
$V_{DRM}$ $V_{RRM}$	Repetitive peak off-state voltage Repetitive peak reverse voltage	tp=10ms		125	800		1800	V
$I_{DRM}$ $I_{RRM}$	Repetitive peak current	at $V_{DRM}$ at $V_{RRM}$		125			40	mA
$I_{TSM}$	Surge on-state current	10ms half sine wave $V_R=0.6V_{RRM}$		125			9.5	kA
$I^2t$	$I^2t$ for fusing coordination						451	A <sup>2</sup> s*10 <sup>3</sup>
$V_{TO}$	Threshold voltage			125			1.40	V
$r_T$	On-state slope resistance						0.68	mΩ
$V_{TM}$	Peak on-state voltage	$I_{TM}=1400\text{A}$ , $F=15\text{kN}$		125			2.35	V
dv/dt	Critical rate of rise of off-state voltage	$V_{DM}=0.67V_{DRM}$		125			500	V/ $\mu$ s
di/dt	Critical rate of rise of on-state current	$V_{DM}=67\%V_{DRM}$ to 1000A, Gate pulse $t_r \leq 0.5\mu\text{s}$ $I_{GM}=1.5\text{A}$		125			1200	A/ $\mu$ s
$Q_{rr}$	Recovery charge	$I_{TM}=1000\text{A}$ , $t_p=2000\mu\text{s}$ , $di/dt=-60\text{A}/\mu\text{s}$ , $V_R=50\text{V}$		125		460		$\mu\text{C}$
$t_q$	Circuit commutated turn-off time	$I_{TM}=1000\text{A}$ , $t_p=2000\mu\text{s}$ , $V_R=50\text{V}$ $dv/dt=30\text{V}/\mu\text{s}$ , $di/dt=-60\text{A}/\mu\text{s}$		125	18		50	$\mu\text{s}$
$I_{GT}$	Gate trigger current				40		250	mA
$V_{GT}$	Gate trigger voltage	$V_A=12\text{V}$ , $I_A=1\text{A}$		25	0.9		2.5	V
$I_H$	Holding current				20		400	mA
$V_{GD}$	Non-trigger gate voltage	$V_{DM}=67\%V_{DRM}$		125	0.3			V
$R_{th(j-c)}$	Thermal resistance Junction to case	DC: double side cooled					0.035	°C/W
$R_{th(c-h)}$	Thermal resistance case to heat sink	Clamping force 15kN					0.008	
$F_m$	Mounting force				10		20	kN
$T_{stg}$	Stored temperature				-40		140	°C
$W_t$	Weight					240		g
Outline	P08							




Fig1




Fig2




Fig3




Fig4





Fig5



Nlps reserves the right to change specifications without notice.