

Features

- Center amplifying gate
- Metal case with ceramic insulator
- Low on-state and switching losses

$I_{T(AV)}$ **960A**
 V_{DRM}/V_{RRM} **400 ~ 1000V**
 I_{TSM} **13 kA**
 I^2t **845 10³A²S**

Typical Applications

- AC controllers
- DC and AC motor control
- Controlled rectifiers

SYMBOL	CHARACTERISTIC	TEST CONDITIONS		T _J (°C)	VALUE			UNIT
					Min	Type	Max	
I _{T(AV)}	Mean on-state current	180° half sine wave 50Hz Double side cooled,	T _C =70°C	125			960	A
V _{DRM} V _{RRM}	Repetitive peak off-state voltage Repetitive peak reverse voltage	tp=10ms		125	400		1000	V
I _{DRM} I _{RRM}	Repetitive peak current	at V _{DRM} at V _{RRM}		125			40	mA
I _{TSM}	Surge on-state current	10ms half sine wave		125			13.0	kA
I ² t	I ² t for fusing coordination	V _R =0.6V _{RRM}						845
V _{TO}	Threshold voltage			125			0.80	V
r _T	On-state slope resistance							0.35
V _{TM}	Peak on-state voltage	I _{TM} =1800A, F=15kN		25			1.80	V
dv/dt	Critical rate of rise of off-state voltage	V _{DM} =0.67V _{DRM}		125			1000	V/μs
di/dt	Critical rate of rise of on-state current	V _{DM} = 67%V _{DRM} to 1500A, Gate pulse t _r ≤ 0.5μs I _{GM} =1.5A		125			100	A/μs
Q _{rr}	Recovery charge	I _{TM} =1000A, tp=4000μs, di/dt=-20A/μs, V _R =100V		125		1100		μC
I _{GT}	Gate trigger current	V _A =12V, I _A =1A		25	35		300	mA
V _{GT}	Gate trigger voltage				0.8		2.5	V
I _H	Holding current				20		250	mA
I _L	Latching current						500	mA
V _{GD}	Non-trigger gate voltage	V _{DM} =0.67V _{DRM}		125			0.3	V
R _{th(j-c)}	Thermal resistance Junction to case	D.C. double side cooled Clamping force 15kN					0.035	°C/W
R _{th(c-h)}	Thermal resistance case to heat sink						0.008	
F _m	Mounting force				10		20	kN
T _{vj}	Junction temperature				-40		125	°C
T _{stg}	Stored temperature				-40		140	°C
W _t	Weight					240		g
Outline	P08							




Fig1




Fig2




Fig3




Fig4




Fig5




Fig6




Fig7




Fig. 8

Outline:

